

# BLUEROCK Magnetic Drill Comparison Chart

	TYP-28A	BRM-35A/A-B	BRM-60A-B	TYP-75
<b>Max Drilling Diameter</b>	1-1/2" / 35mm	1-1/2" / 35mm	2-1/4" / 60mm	3" / 75mm
<b>Max Drilling Depth</b>	2"	2"	2"	2"
<b>Tool Holder</b>	Direct arbor with 3/4" Weldon Shank tool holder	Direct arbor with 3/4" Weldon Shank tool holder	MT3 arbor with MT2/MT1 adapters & 3/4" Weldon Shank adapter	Direct 1-1/4" Weldon Shank with 3/4" Weldon Shank adapter
<b>Speed</b>	640 RPM	595 RPM	Dual Speed: 260 & 470 RPM	Dual Speed: 260 & 470 RPM
<b>Reversible</b>	—	—	✓	✓
<b>Stroke</b>	2" (annular cutter only)	6.5" (annular cutters and short twist bits only)	9" (annular cutters and some twist bits)	9" (annular cutters and some twist bits)
<b>Drill Chuck Compatible</b>	—	✓	✓	✓
<b>Drill Weight</b>	24 lbs	28 lbs	51 lbs	52 lbs
<b>Weight Shipped</b>	38 lbs	39 lbs	68 lbs	72 lbs
<b>Amps</b>	7 amp	10 amp	15 amp	15 amp
<b>Watts</b>	950W	1200W	1850W	1850W
<b>Voltage</b>	120v 50/60Hz	120v 50/60Hz	120v 50/60Hz	120v 50/60Hz
<b>Magnetic Base Size</b>	3-1/8" x 6-3/8"	3-1/8" x 7"	9" x 4.5"	9" x 4.5"
<b>Magnetic Adhesion</b>	2600 lbs	2600 lbs	4050 lbs	4050 lbs
<b>Carrying Case</b>	✓	✓	✓	✓
<b>Machine Size</b>	Small/Compact 10" x 6" x 10"	Medium/Lightweight Lowered: 12" x 4-1/2" x 15-1/4" Raised: 12" x 4-1/2" x 20-1/2"	Large/Heavy Lowered: 14-1/2" x 7-1/2" x 19" Raised: 14-1/2" x 7-1/2" x 28"	Large/Heavy Lowered: 14-1/2" x 7-1/2" x 17-1/2" Raised: 14-1/2" x 7-1/2" x 26"